AnglerFish





Miniature LED flasher

Features

- ▶ Self-contained 380-lumen LED
- ▶ Visible up to 5 nmi to aid in vehicle recovery
- ▶ Built-in daylight sensor
- ▶ Double burst every two seconds standard; other flash rates optional
- ▶ 1.000-m rated
- ▶ Easily mounts to masts
- Connects to power and control via a standard 3-pin connector or threaded boss
- ▶ Optional smart battery backup accessory in a PC/104 form factor

Technical specifications on reverse.

AnglerFish

Technical Specifications

	CDECIFICATION
PARAMETER	SPECIFICATION
Model Number	AR 102
OPTICAL	
Visible Range	3–5 nmi
Beam Angle	360°
Flash Rate	Double burst every two seconds standard
Output	380 Lm
ELECTRICAL	
Input Voltage	5-40 VDC
Power Draw	.55 W @ 24 VDC
Current Draw	23 mA average; 228 mA max @ 24 V
INTERFACE	
Connectors	MCBH3M or threaded boss to fit MCBH 7/16–20 hole
MECHANICAL	
Weight	41 g in air; 30 g in seawater
Materials	Delrin housing; acrylic window
ENVIRONMENTAL	
Depth Rating	1,000 m (3,300 ft)
Temperatures	-10°C to 40°C operating















