

Remora Torch

LIGHTING
SERIES



Compact LED light

Features

- ▶ High-output, 10,000-lumen continuous, dimmable torch light for professional imaging applications
- ▶ Optimized for AUV imaging applications; designed for OceanServer Iver3 AUVs and can be customized for other vehicles
- ▶ Integral Iver penetrator plug or optional bulkhead connector
- ▶ Extremely compact package with integral power-efficient driver electronics
- ▶ 300-m-rated
- ▶ Wide angle, even light distribution
- ▶ User-settable PWM dimming frequency allows flicker-free operation for various video frame rates
- ▶ Various white temperatures and monochrome color options
- ▶ Durable, hard-anodized 6061 aluminum housing
- ▶ Wide input voltage supply

Technical specifications on reverse.

Arctic Rays specializes in deep-sea lighting and imaging systems and other custom solutions specifically for use on AUVs, ROVs, manned submersibles and other offshore and underwater structures.

Think deep.
arcticrays.com • 1.321.610.4635



ARCTIC RAYS
SUBSEA TECHNOLOGIES

Remora Torch

Technical Specifications

PARAMETER	SPECIFICATION
Model Number	AR 114
OPTICAL	
Operating Mode	Continuous torch; dimmable
Color channels	One
Output	10,000 Lm @ 5,700K
Color Temperature	4,000K 5,700K standard 6,500K deep blue 450 nm blue 470 nm green 525 nm far red 730 nm
Color Rendering Index	70 min. standard; optional 80 min., 90 min.
Beam Angle (FWHM)	100° standard; 65° optional
ELECTRICAL	
Voltage	12-38 VDC standard; other voltage ranges optional
Power	105 W max
Max Input Current	4.2 A @ 24V
Dimming Method	Pulse width modulation; 0-100% duty cycle in 1% increments
PWM Frequency	44 kHz
Efficacy	100 Lm/W
INTERFACE	
Connector	Subconn MCBH4M or Impulse LPMBH4M
Control	Multidrop RS232 or RS485 (2-wire) serial; 254 soft addresses
MECHANICAL	
Weight	475 g in air; 230 g in seawater
Materials	6061-T6 aluminum housing (AHC black); acrylic window
ENVIRONMENTAL	
Depth Rating	300 m (984 ft)
Temperatures	-10°C to 40°C operating; -25°C to 85°C storage

